



STANDARD CONFIGURATION & OPTIONS SPECIFICATIONS

Version 1.5_ENG, September 2023, valid for orders under Pricelist A2024



TECHNICAL DATA

- Hull length: 7,29 m / 23' 11"
- Beam: 2,50 m / 8' 2"
- Displacement (MLC*) with standard keel: 1000 kg / 2205 lbs
- Standard keel
 - Draft: lifted keel 0,25 m / 9", lowered keel 2,00 m / 0,82 ft, 6' 7"
 - Weight: 300 kg / 661 lbs
- Shallow keel
 - Draft: lifted keel 0,55 m / 1'9", lowered keel 1,15 m / 3'9"
 - Weight: 430 kg / 948 lbs
- Mainsail (laminated): 24,0 m² / 258 ft²
- Jib (laminated): 15,3 m² / 165 ft²
- Gennaker (nylon): 58,0 m² / 624 ft²
- Mast (carbon fibre): 10 m / 32' 10"
- Boom (carbon fibre): 3,50 m / 11' 6"
- Bowsprit (carbon fibre): 2,08 m / 6' 10"
- Hull/deck material: Vacuum-infused GRP
- Insubmersibility volume: 1,6 m³ / 57 ft³
- CE design category: C8
- Naval architect: Manuard YD
- Industrial design: SITO
- Concept and R&D: Seascape
- Air draft: 11,26 m / 36' 11"
- Height on trailer: 3,4 m / 11' 2" - w/o mast 2,25 m / 7' 5"
- Length overall on the trailer: 10 m / 32' 10" - w/o mast 9,20 m / 30' 2"

STANDARD CONFIGURATION

CONSTRUCTION

- Hull and deck constructed with vacuum infusion of Vinyl ester resin, Airex PVC foam and Soric GRP sandwich with unidirectional and multiaxial laminates
- The hull is reinforced with infused GRP stringers in the keel and in bow sections
- The deck comes with moulded non-skid

- Two transoms hung rudders built of GRP foam sandwich and aluminium casings
- Hull and deck are moulded in single tone off-white RAL 9003
- The hull is prepared for the application of antifouling
- Underwater areas finished in gelcoat and faired, with possible flaws and imperfections, prepared for sanding and application of epoxy primer and antifouling

KEEL ARRANGEMENT

- Swinging keel build in GRP vinyl ester composite with lead bulb insert
- Custom made manually operated stainless steel keel winch
- Keel head and edges protected with epoxy primer
- Slotstrip / keel lips closing the exit of the keel box

DECK EQUIPMENT

- 45 cm / 18-inch high pushpit, pulpit and stanchions with a single lifeline
- Two lifeline cushions
- Stainless steel bow and stern mooring cleats
- Stainless steel chain plates for shrouds and forestay
- Coachroof mounted opening hatch 58 x 58 cm / 23 x 23 inches for access to the cabin
- 2x Harken STA20 winches on the coachroof
- 2x Ronstan jib tracks with blocks on the coachroof
- Spinlock clutches for halyards and control lines
- Ronstan blocks and cleats for other controls
- Carbon-look tiller with Ronstan tiller extension
- 2x First branded rope bags from Outils Océans
- Tempered glass windows on each side of the coachroof
- Spacious storage under the cockpit area with two big hatches
- Bilge pump
- Attachment point for indoor/outdoor table in the cockpit
- Attachments for engine bracket
- A numeric lock for the main companionway

MAST & RIGGING

- Compotech high-quality carbon fibre mast and boom with one set of swept-back spreaders, all build in high-quality carbon fibre
- Carbon parts UV protected
- Continuous 1x19 standing rigging with bottle screw adjusters

- 8:1 outhaul and two reefs
- Retractable carbon bowsprit controlled from the cockpit
- One tapered mainsheet with mainsheet tackle of ball bearing low
- Friction blocks
- 12:1 boom vang
- Two jib sheets
- One 2:1 Dyneema main halyard
- One Dyneema jib halyard
- One Dyneema fractional spinnaker halyard
- Two reef lines
- One bowsprit control line
- One spinnaker tack line
- Two tapered spinnaker sheets
- One 8:1 cunningham control line
- Facnor FLT jib furler with the furling line
- Mast transport cover

STANDARD SAILS

- North Sails mainsail – 24 m²/258 ft², Pentex laminate, triradial cut, with two reefs and bolt rope
- North Sails furling jib – 15,3 m²/164 ft², Pentex laminate, triradial cut with vertical battens and hanks on the luff

INTERIOR

- Bulkheads and furniture lightly covered with a satin finish top paint and white RAL 9003 gel coat on the moulded parts for light, clean and low maintenance finish

Bow section:

- Double V-berth with insubmersibility volume underneath
- Light and ventilation through big foredeck hatch

Central saloon area:

- Bright and spacious main cabin area with large companionway hatch
- Long berths/benches with storage place under the front 1.5 m and insubmersibility volume under the rest
- Folding covers for the storage area
- Plexiglas companionway washboard and sliding hatch
- EVA foam padding on the floor
- Two Wichard folding pad eyes for lifting straps on the keel-box
- Indoor/outdoor table attachment point on the top of keel-box

OPTIONS SPECIFICATIONS

SHALLOW SWING KEEL

- Shallow keel version, with reduced draft - lifted position 0,55 m / 1'10", lowered position 1,15 m / 3' 9"
- Increased weight for comparable stability to standard deep keel: 430 kg / 948 lbs
- Shallow keel in lifted position sticks out of the hull for 0,3 m / 1'; thus, trailer upgrade for shallow keel is required, and the boat can not be beached anymore
- Operated by standard manual stainless steel keel winch
- GRP vinyl ester composite shell with lead insert
- Keel head and edges protected with epoxy primer
- Slot strip/keel lips closing the keel slot
- Possible retrofit from deep to the shallow keel version and vice versa

SAILS

NORTH SAILS FRACTIONAL GENNAKER IN A CHOSEN COLOUR

- Fractional soft luff gennaker/asymmetric spinnaker
- Norlon RipStop Nylon 90, 58,00 m² / 624 sq. ft.
- Colour options – WHITE, RED and BLACK

NORTH SAILS A5 FURLING GENNAKER & FURLER IN A CHOSEN COLOUR

- Tight luff fractional A5 furling reacher,
- Facnor FX 1500+ furler set with spliced continuous furling line
- Norlon RipStop Nylon 150, 42,50 m² / 458 sq. ft.
- Colour options – WHITE, RED and BLACK

NORTH SAILS J2 HEAVY JIB

- Smaller heavy J2 furling jib for standard jib furler
- Biradial cut, strong laminate material, 12,10 m² / 130 sq. ft.

NAVIGATION & ELECTRONICS

COMPASS PLASTIMO CONTEST 101

- Compass mounted on bulkhead next to the companionway
- Compass light connected to navigation lights switch

ELECTRIC PACK (12V)

- Seanapps mobile application and GSM/GPS tracker for live control of your boat (trip logs, anchoring) and real-time alerts (entrance sensor & battery status) with a 1-year subscription
- AGM 12V/70 Ah battery
- Sunbeam Tough series walkable 55W solar on the cabin in front of the mast with smart MPPT solar panel regulator for up to 30% better panel efficiency and Bluetooth connectivity
- Interior indirect LED lighting
- Control panel with voltmeter display switches and box under the companionway
- Double USB plug & standard 12V plug
- Masthead tricolour navigation & anchor lights with switches on the control panel

GARMIN INSTRUMENTS PACK

- GMI 20 large and bright 4" QVGA colour displays with LED backlighting, installed on the coachroof
- Airmar DST810 depth, speed and temperature transducer
- gWind race wired wind transducer
- NMEA2000 backbone kit and wiring
- Dedicated switch on the control panel

RAYMARINE ST1000 BASIC AUTOPILOT PACK

- Autonomous Raymarine ST1000 tiller pilot
- Deck and tiller attachment points
- Electrical wiring with a switch on the control panel

RAYMARINE EVO100 PERFORMANCE AUTOPILOT PACK

- Raymarine EV100 tiller pilot with EV-1 sensor core
- P70 display mounted on bulkhead next to the companionway
- Raymarine S100 Remote Control
- Deck attachment points
- Electrical wiring for the pilot

230V CHARGING PACK

- 230V charger with fuse
- Shore cable socket in the cockpit
- Shore cable (15 m) with adapter for standard 230V socket
- Internal 230V socket
- Not available in the USA

115V CHARGING PACK

- 115V charger with fuse
- External shore cable socket in the cockpit
- Shore cable (49 ft)
- Internal 115 V socket
- Available only in the USA

INTERIOR

CHEMICAL TOILET

- Portable Thetford 335 port-a-potty chemical toilette
- Anticipated storage place in saloon under sliding berth extensions, limited and fixed with the keel-box

COMFORT PACK IN A CHOSEN COLOUR

- Faux leather cushions on the front V-berth and saloon side benches
- Colour options – GREY and TURQUOISE
- Wooden sliding berths extensions on both sides of the keel box with cushions in the chosen colour; they extend the bench to a comfortable berth or offer extra seats; when not in use, panels are stored under the entrance and enable free movements in the saloon
- Indoor/outdoor table with storage bag in grey

FIRST SE CREW BAGS (4 PIECES) IN A CHOSEN COLOUR

- Water repellent PVC easy-to-hang FIRST crew bags
- Attachment points for all two bags in the saloon and two above front V-berth
- FIRST SE handles in red
- Colour options – GREY, WHITE, BLUE or RED

OTHER OPTIONS

REMOVABLE ENGINE BRACKET

- Removable engine bracket mounted on the stern of the boat
- For outboards with the long shaft, up to 6 HP

MOORING PACK

- Spade A60 aluminium anchor (4,5 kg / 10 lbs)
- 40 m/12 mm 131' 3" / 0,47inch rope for the anchor with 10m / 32'10" lead insert

- Robust Outils Océan storage bag for the anchor and rope
- Mooring lines with spliced ends, 10m/12mm 32' 10"/0,47 inch, 4x
- Square fenders Outils Océan with fixation ropes, 4x

CUSTOM BATHING LADDER

- Marine-grade stainless steel bathing ladder
- Robust, made in one single piece (non-foldable), with a handle for easier climbing
- Attached on the stern of the boat, between both rudder blades
- When not in use, easily stored under the cockpit
- Compatible with "Stern bench & steering system cover" option

INDOOR & OUTDOOR TABLE

- Wooden foldable table, which can be used in the salon or cockpit
- Modular aluminium central leg, powder-coated in white
- Fixation point on the top of the keel box in the salon and on the cockpit floor
- Water repellent PVC storage bag for all the parts in GREY

STEERING SYSTEM COVER & BENCH ON THE STERN

- The protective cover of the steering system, convenient for clubs and sailing schools
- Comfortable bench on the aft of the cockpit for additional seating and sunbathing area in cruising mode
- Very light option, build in GRP with Honeycomb core and moulded antiskid
- Easily removable equipment secured with pins to reduce weight in racing mode

SPINLOCK TILLER EXTENSION

- Spinlock tiller extension EA1200DS, in lieu of standard Ronstan Battlestick
- Connected to the tiller with a rubber joint, which keeps it upright
- Especially recommended option for shorthanded sailing and together with the autopilot options

MARINE BEAN BAG

- Rectangular bean bag for additional comfort on and below the deck
- Spliced fixation rope with plastic snap-shackle
- Colours combinations – GREY/WHITE and GREY/BLUE

CUSTOM COLOUR HULL WRAP

- Hull wrap with folio in custom colour
- If shipped in the container, the “not applied” version should be ordered
- The option is not a transport protection wrap, but a decoration

COVERS & BAGS

LAZYBAG

- Lazybag with smart solutions for easier mainsail handling and storage
- Ready-to-roll while under sails, designed to pull lazy jacks to the mast
- Split support battens for easier transport and storage
- Spliced Dyneema lazy jacks with composite shackles attachments
- Zips along with the bag for the sun tent option

SUN TENT (LAZYBAG ASSEMBLY)

- Tent shading option for easy installation on the lazy-bag with zipper
- Elastics for attachment on the railing
- Sunbrella fabric

SUNSHADE WITH POLES

- Shading option installed over the mainsail and boom
- Tent poles for extension and fixation of the cover
- Elastics for fixation on the railing
- Tyvek material

TRANSPORTATION

LIFTING STRAPS

- Three lifting straps connected in one single lifting point,
- Possible craning with stepped mast, as the boat will tilt slightly forward
- Safety dyneema loop around the mast
- Certified lifting equipment
- Same arrangement, with different lengths of the straps of the shallow keel

PROVISIONAL MAST CRANE (A-FRAME)

- Simplifying stepping of the mast without a crane
- Lightweight aluminium powder-coated telescopic A-frame providing provisional crane
- Spliced dyneema ropes with hooks for aft fixations
- Dedicated transport and storage bag

LOK CUSTOMISED TRAILER WITH EQUIPMENT

- Customised trailer with galvanised steel frame
- Homologated for max 1600 kg towing weight
- Single-axis with low profile tires for easier slip launching
- Knott equipment and hand break
- Brakes and dampers for 100km/h admissibility
- Integrated brake drum washing system
- Mast support with a manual winch for launching/recovering the boat
- Aft GRP cradles with EVA foam padding
- Rubber rollers in the middle and pads in the front for easier slip launching
- Front support wheel & aft support leg
- Standard European 13-pin connector
- Spare tire
- Trailer straps pack with pads
- Available only for Europe

CUSTOM BOAT CRADLES FOR THE TRAILER

- Two GRP cradles with EVA foam padding, supporting boat's stern on the trailer
- Already included with LOK Trailer option

*MLC: Mass of the boat in Light Craft Condition includes the weight of the boat in the standard ready-to-navigate configuration, keel, standard equipment, sails (mainsail & jib) and engine

Beneteau First 24 SE – Seascape edition_Standard Configuration & Options Specifications_Version 1.5_ENG, September 2023

Seascape d.o.o., Podpeč 53, 1352 Preserje, Slovenia.

Specifications and descriptions are provided only for your guidance and are subject to change without prior notice.

www.beneteau.com

www.seascape-edition.com